



Kroon-Oil Product recommendation

Isuzu - Trooper 2.0 (1984-1985)

Recommended product	ENGINE, G200Z System capacity: 4,2 liter Filter: 0,6 liter <u>Multifleet SCD 10W</u> Usage: Severe, change every 5000 km Usage: Normal, change every 10000 km / 6 months
	<u>Motor Oil HDX 10W</u> Usage: Severe, change every 5000 km Usage: Normal, change every 10000 km / 6 months
Good alternatives	<u>Motor Oil HDX 20W20</u> Usage: Severe, change every 5000 km Usage: Normal, change every 10000 km / 6 months
Recommended product	DIFFERENTIAL, REAR RemarksFor limited slip differentials add GM part no. 1052358. System capacity: 1,3 liter <u>Transmission Oil SP 1051</u> Usage: Severe, check every 10000 km / 6 months Usage: Severe, change every 20000 km Usage: Normal, check every 10000 km / 6 months Usage: Normal, change every 40000 km / 24 months
	<u>Gearlube GL-5 80W90</u> Usage: Severe, check every 10000 km / 6 months Usage: Severe, change every 20000 km Usage: Normal, check every 10000 km / 6 months Usage: Normal, change every 40000 km / 24 months
Good alternatives	
Recommended product	DIFFERENTIAL, FRONT RemarksFor limited slip differentials add GM part no. 1052358. System capacity: 0,8 liter <u>Transmission Oil SP 1051</u> Usage: Normal, check every 10000 km / 6 months Usage: Normal, change every 40000 km / 24 months
	<u>Gearlube GL-5 80W90</u> Usage: Normal, check every 10000 km / 6 months Usage: Normal, change every 40000 km / 24 months
Good alternatives	
Recommended product	TRANSMISSION, MANUAL/TRANSFERBOX, 4/1 System capacity: 2,5 liter <u>Multifleet SCD 10W</u> Usage: Normal, check every 10000 km / 6 months Usage: Normal, change every 40000 km / 24 months
	<u>Motor Oil HDX 10W</u> Usage: Normal, check every 10000 km / 6 months Usage: Normal, change every 40000 km / 24 months
Good alternatives	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. This sheet refers to an MSDS, which is a part of the Product Information System.



Recommended product

HYDRAULIC BRAKE SYSTEM

Drauliquid DOT 3

Usage: Normal, change every 12 months

POWER STEERING

System capacity: 1 liter

Recommended product

ATF Dexron II-D

Usage: Normal

GREASE POINTS/NIPPLES, BALL JOINTS

Recommended product

Labora Grease

Usage: Normal, change every 40000 km / 24 months

Good alternatives

Lithep Grease 2

Usage: Normal, change every 40000 km / 24 months

GREASE POINTS/NIPPLES, PROPELLER SHAFT JOINTS

Recommended product

MoS2 Grease 2

Usage: Normal, check every 10000 km / 6 months

COOLING SYSTEM

System capacity: 7,6 liter

Recommended product

Coolant -38 NF

Usage: Normal, change every 24 months

Good alternatives

Coolant -26

Usage: Normal, change every 24 months

STEERING GEAR

System capacity: 0,2 liter

Recommended product

Gearlube GL-5 80W90

Usage: Normal, check every 20000 km / 12 months

Good alternatives

Unigear HS GL-2/GL-5 80W90

Usage: Normal, check every 20000 km / 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. This sheet refers to an MSDS, which is a part of the Product Information System.