



Kroon-Oil Product recommendation

Isuzu - Trooper 2.8 TD (1988-1990)

ENGINE, 4JB1T

System capacity: 4,3 liter

Filter: 0,5 liter

Recommended product

Torsynth Diesel 10W40

Usage: Normal, change every 5000 km / 6 months

Good alternatives

Torsynth 10W40

Usage: Normal, change every 5000 km / 6 months

Bi-Turbo 15W40

Usage: Normal, change every 5000 km / 6 months

DIFFERENTIAL, REAR, LIMITED SLIP

System capacity: 1,8 liter

Recommended product

Racing Gearlube 75W140

Usage: Normal, check every 15000 km / 12 months

Usage: Normal, change every 60000 km / 48 months

DIFFERENTIAL, FRONT

System capacity: 1,5 liter

Recommended product

Transmission Oil SP 1051

Usage: Severe, check every 15000 km / 12 months

Usage: Severe, change every 20000 km

Usage: Normal, check every 15000 km / 12 months

Good alternatives

Usage: Normal, change every 60000 km / 48 months

Gearlube GL-5 80W90

Usage: Severe, check every 15000 km / 12 months

Usage: Severe, change every 20000 km

Usage: Normal, check every 15000 km / 12 months

Usage: Normal, change every 60000 km / 48 months

TRANSMISSION, MANUAL, 5/1

System capacity: 2,95 liter

Recommended product

Asyntho 5W30

Usage: Normal, check every 15000 km / 12 months

Usage: Normal, change every 60000 km / 48 months

Good alternatives

Torsynth 10W40

Usage: Normal, check every 15000 km / 12 months

Usage: Normal, change every 60000 km / 48 months

TRANSFERBOX

System capacity: 1,45 liter

Recommended product

Asyntho 5W30

Usage: Normal, check every 15000 km / 12 months

Usage: Normal, change every 60000 km / 48 months

Good alternatives

Torsynth 10W40

Usage: Normal, check every 15000 km / 12 months

Usage: Normal, change every 60000 km / 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. This sheet refers to an MSDS, which is a part of the Product Information System.



Recommended product

HYDRAULIC BRAKE SYSTEM

Drauliquid DOT 3

Usage: Normal, change every 12 months

Recommended product

POWER STEERING

System capacity: 1 liter

ATF Dexron II-D

Usage: Normal, change every 45000 km / 36 months

Recommended product

GREASE POINTS/NIPPLES, PROPELLER SHAFT JOINTS

MoS2 Grease 2

Usage: Normal, check every 10000 km / 6 months

GREASE POINTS/NIPPLES, FREEWHEEL HUBS

We are unable to give a standard recommendation for this component. Please contact our service department. Telephone: +31 (0)546-818165 E-mail: technischendienst@kroon-oil.nl

Recommended product

GREASE POINTS/NIPPLES, WHEEL BEARINGS

Labora Grease

Usage: Normal, change every 40000 km / 24 months

Good alternatives

Lithep Grease 2

Usage: Normal, change every 40000 km / 24 months

Recommended product

COOLING SYSTEM

System capacity: 10,3 liter

Coolant -38 NF

Usage: Normal, change every 24 months

Good alternatives

Coolant -26

Usage: Normal, change every 24 months

Recommended product

STEERING GEAR

System capacity: 0,2 liter

Transmission Oil SP 1051

Usage: Normal, check every 30000 km / 24 months

Good alternatives

Gearlube GL-5 80W90

Usage: Normal, check every 30000 km / 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. This sheet refers to an MSDS, which is a part of the Product Information System.